REGON: 521473146

NIP: 7952568415



KAWMET.PL

DECLARATION OF PERFORMANCE NO. W17PANORAMA-16,1/03/2022 IN ACCORDANCE WITH THE REGULATION UE 305/2011



1	Unique identification code of the product type	KAWMET W17 Panorama (16,1 kW) ECO
2	Intended use of the product	Room heater burning solid fuel without hot water supply
3	Name and address of the manufacturer	ODLEWNIA KAW-MET MAREK KAWIŃSKI Sp.z o.o. Zadąbrowie 311, 37-716, Orły, Polska
4	Name and address of the authorized representative	N/A
5	System of AVCP	System 3
6	Name and identification number of the notified body	OIL AND GAS INSTITUTE- National Research Institute, 25a Lubicz Str. 31-503 Cracow, POLAND / Notified body No. 1450
	Test report no.	3210 A9 16 / 3210 B9 16

1est report no. 3210 A9 16 / 3210 B9 16		
DECLARED PERFORMANCE		
ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONIZED TECHNICAL SPECIFICATION
Fire safety:		
Reaction to fire	A1	
Distance to combustible materials	Minimum distances (mm): Floor = 0 Front, rear, sides, ceiling = 1000 • Combustable materiels inside the surround must be covered by insulation as decribed in the manual	
Risk of burning fuel falling out	Pass	.C:2007
Safety of filling the device with fuel	Pass	
Equipping the product with adjustable and properly marked combustion air setting devices	Pass	
Cleanability	Pass	8 4 4 A
Correct and effective operation of the device	Pass	2005
Release of dangerous substances	NPD	41:24 42:24 40:32
Electrical safety	NPD	EN 13229:2001 EN 13229:2001/A1:2003 EN 13229:2001/A2:2004 EN 13229:2001/AC:2004/AC:2007
Nominal heat output	16,1 kW	
Room heating output	16,1 kW	
Water heating output	NPD	
Energy efficiency (η _{th,nom})	71,2%	
Emission of combustion products, CO (13% O ₂)	0,16% / 1947 mg/m³	
Flammability	1 h	
Surface temperature	Manipulation handles: Primary air adjustment handle: 127,0 °C Secondary air adjustment handle: 55,1 °C Damper handle: 45,5 °C • The manufacturer provides tools to ensure	
Flue gas temperature at nominal heat output	safe operation of the device 386,1 °C	
Maximum operating pressure	NPD	
Mechanical resistance	NPD	
Fuel type	Hardwood (moisture ≤20%)	USER MANUAL

The performance of the product identified in point 1 in conformity with the declared performance in point 7.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. in accordance with the regulation UE 305/2011

ODLEWNIA "KAW-MET"

MAREK KAWIŃSKI SP. Z O.O.

37-716 Orły, Zadąbrowie 311

NIP 7952568415, REGON 521473146

- John Colon Colon